

UPS

Manufacturer	SOCOMEK
Model	NRT-U3000C
Performance (kVA/kW)	3 kVA / 2.1 kW

Nominal Voltage

Input (V)	230 V (Ph+N)
Output (V)	230 V (Ph+N)

Nominal Current

Input (A)	10.3 A (Full Charged)
Output (A)	13 A

Static Bypass

<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
If Yes, Maximum allowed I ² t (A ² s)	10000

Short circuit capability

Short time	
Current (A)	58 A
Maximum time (s)	100 ms
Long time	
Current (A)	58 A
Maximum time (s)	100 ms

Maximum thermal overload

Current (A)	13.05 A
-------------	---------

Installation data

Cable cross-section	Input IEC 320-C20 (16 A) / Output 6 x IEC 320-C13 (10 A) + 1 x IEC 320-C13 (10 A)
Mains protection	20A AC Breaker (1 Pole) curve C
Auxiliary Mains protection	20A AC Breaker (1 Pole) curve C
Common Input protection	20A AC Breaker (1 Pole) curve C
>discr. Protection	10 A B curve
Noise (dBA)	45 dB(A)
Maximum Heat loss	1468 Btu/hr



Coromatic